


OFFICE OF THE MARION COUNTY SURVEYOR
SECTION RECORD CORNER
SECTION 13 TOWNSHIP 14 RANGE 4
DATE: --7-29-99-- 2-26-04
PARTY CHIEF: Kiste
CREW: _____
TYPE OF MARKER: Harrison
METHOD OF ESTABLISHMENT: County: 9-12-94

IN. S.P.C. E ZONE, NAD 83
NAME: 14041302
N: 490574.7080(m)
E: 68400.2310(m)



Original post set 1820 by Hendricks with witnesses: 36" white oak S 24 E 7 links, 15" beech N 1 W 22 links per Marion County Atlas pg. 9. Hosbrook 11-27-1849 called witnesses: 18" hickory N 12 E 37 links and 16" hickory SW (no distance recorded), 6" beech S 50 W 47 links per Franklin Township Legal Survey Book pg. 22. Hosbrook 2/10 & 2/11-1852 called witnesses: 8" beech S 49 W 45 links, 16" hickory N 13 E 38 links per Franklin Township Legal Survey Book pg. 23. 11-25-59 railroad spike called in pavement. 9-26-61 called same. 12-30-71 called railroad spike this location. 5-8-72 called same. 7-14-75 called same. Excavated 6-10-85 set Harrison. Re-tied and raised to surface 9-12-94. Re-tied by Kiste 7-29-99.

HC441302

REF.	DISTANCE	DESCRIPTION
1.	25.29'	PK nail W fence post
2.	39.73'	PK nail S PwP no# 2'up
3.	54.57'	'Old' PK nail E PwP#24-769 1'up
4.	24.95'	1' pipe extending 12' above ground
5.	53.48'	Cut 'x' E-rim manhole
6.	138.23'	PK nail N PwP#48-768 6'up
7.	94.15'	PK nail S PwP#35-768 1'up
8.	54.85'	SW corner wooden shed
9.	93.55'	SE corner block shed